




Three Phase Power supplies			
CE/UL			
	240W (Model DRT-240-24)	480W (Model DRT-480-24)	960W (Model DRT-940-24)
Part No. 24VDC output	45703K/24S-3Phase	45704K/24S-3Phase	45705K/24S-3Phase
Input volt. Range	340-550VAC; 3-phase 4 wires		
Output Volt./current	24VDC/10.0A	24VDC/20A	24VDC/40A
Size W x H x D	125.5x125.5x100mm	227x125.5x100mm	276x125.2x100mm

AC to DC Switching power supply 1, 2, 3, outputs




Part No. RP-MT99
Din 35mm bracket

Part No.	O/P Volt			Rated Load (Current) CE, UL		
	V1	V2	V3	V1	V2	V3
	VDC	VDC	VDC			
RP30352SV	+5V	+12V	-12V	3.5A	1A	0.5A
RP30502SV	+5V	+12V	-12V	4A	2A	0.5A
RP20843FV	+15V	-15V	--	2.8A	2.8A	--

Please visit www.esgllc-usa.com for complete specs and additional power supplies

Control Transformers



Transformers

- Open Type Single-phase transformers
- UL-508 and CSA C22.2 n
- Isolation class A (105 °C)
- **VA sizes offered: 50-2000**
- File: E169331 (S)

Please call for larger sizes

Voltage		Part No.	VA
Primary (AC)	Secondary (AC)		
208/230/460 (No fusing on the primary)	115	T1-UL-50	50
		T1-UL-75	75
		T1-UL-100	100
		T1-UL-150	150
		T1-UL-300	300
		T1-UL-400	400
		T1-UL-500	500