

UL1077 and UL 508 approved for manual motor starting



Features:

Hydraulic-Magnetic Technology
 Always holds 100% rated current independent of ambient temperature
 Always trips at 125% of rated current independent of ambient temperature
 Immediate resetting after trip (no cooling down time is necessary)
 Compact 13 mm width
 Din Rail Mounting

current	curve	1 pole	2 pole	3 pole
1Amp	2	WCB-1P-2-1	WCB-2P-2-1	WCB-3P-2-1
1Amp	9	WCB-1P-9-1	WCB-2P-9-1	WCB-3P-9-1
2Amp	2	WCB-1P-2-2	WCB-2P-2-2	WCB-3P-2-2
2Amp	9	WCB-1P-9-2	WCB-2P-9-2	WCB-3P-9-2
5Amp	2	WCB-1P-2-5	WCB-2P-2-5	WCB-3P-2-5
5Amp	9	WCB-1P-9-5	WCB-2P-9-5	WCB-3P-9-5
10Amp	2	WCB-1P-2-10	WCB-2P-2-10	WCB-3P-2-10
10Amp	9	WCB-1P-9-10	WCB-2P-9-10	WCB-3P-9-10
15Amp	2	WCB-1P-2-15	WCB-2P-2-15	WCB-3P-2-15
15Amp	9	WCB-1P-9-15	WCB-2P-9-15	WCB-3P-9-15
20Amp	2	WCB-1P-2-20	WCB-2P-2-20	WCB-3P-2-20
20Amp	9	WCB-1P-9-20	WCB-2P-9-20	WCB-3P-9-20
25Amp	2	WCB-1P-2-25	WCB-2P-2-25	WCB-3P-2-25
25Amp	9	WCB-1P-9-25	WCB-2P-9-25	WCB-3P-9-25
30Amp	2	WCB-1P-2-30	WCB-2P-2-30	WCB-3P-2-30
30Amp	9	WCB-1P-9-30	WCB-2P-9-30	WCB-3P-9-30
35Amp	2	WCB-1P-2-35	WCB-2P-2-35	WCB-3P-2-35
35Amp	9	WCB-1P-9-35	WCB-2P-9-35	WCB-3P-9-35
40Amp	2	WCB-1P-2-40	WCB-2P-2-40	WCB-3P-2-40
40Amp	9	WCB-1P-9-40	WCB-2P-9-40	WCB-3P-9-40
50Amp	2	WCB-1P-2-50	WCB-2P-2-50	WCB-3P-2-50
50Amp	9	WCB-1P-9-50	WCB-2P-9-50	WCB-3P-9-50
60Amp	2	WCB-1P-2-60	WCB-2P-2-60	WCB-3P-2-60
60Amp	9	WCB-1P-9-60	WCB-2P-9-60	WCB-3P-9-60

Curve 2 - general purpose curve. Trip range: 5-10xrated current

Curve 9 - used when there is rush current. Trip range: 8-12xrated current

151 Discovery Dr. #112
 Colmar, PA 18915
 Email: sales@esgllc-usa.com

UL 489 for Branch Circuit Protection

DIN Rail Mounting; Interrupting Cap.
10,000 Amps
Compact 13mm width (1/2 inch!)
Hydraulic-Magnetic Technology
10 year Warranty

KM curve - trip range: 5-10x rated current

Current	1 pole	2 pole	3 pole
1Amp	WCB-1P-KM-1	WCB-2P-KM-1	WCB-3P-KM-1
2Amp	WCB-1P-KM-2	WCB-2P-KM-2	WCB-3P-KM-2
4Amp	WCB-1P-KM-4	WCB-2P-KM-4	WCB-3P-KM-4
5Amp	WCB-1P-KM-5	WCB-2P-KM-5	WCB-3P-KM-5
10Amp	WCB-1P-KM-10	WCB-2P-KM-10	WCB-3P-KM-10
15Amp	WCB-1P-KM-15	WCB-2P-KM-15	WCB-3P-KM-15
20Amp	WCB-1P-KM-20	WCB-2P-KM-20	WCB-3P-KM-20
25Amp	WCB-1P-KM-25	WCB-2P-KM-25	WCB-3P-KM-25

DC Circuit Breakers

Features:

- Hydraulic-magnetic technology
- Always hold 100% rated current
- Wide range of time delays & operating currents
- Current limiting capabilities
- Ultra compact - 13 mm width module
- Din, Mini-rail or Dual mountable

Poles:	1 and 2 poles
Max. Voltage:	0 VAC, 80 VDC
Max. Interrupting Capacity:	10 kA
Current Rating:	1 A to 50 A
Agency recognition of Approvals:	UL 489A VDE

Ordering Code: WCB-(1 or 2)P-U2- X (x = current 1-63 Amps)

151 Discovery Dr. #112
Colmar, PA 18915
Email: sales@esgllc-usa.com