


Spring Clamp Terminals (Push-in Type)

Part No.	DST2.5	DST4	DST6	DST10
Terminal Pitch	5mm	6mm	8mm	10mm
Height x Width in mm	33x53	33.5 x 59	39.5x73.5	42MM x 76.5 mm
Rated Cross section	2.5mm ²	4mm ²	6mm ²	10mm ²
Wire Strip length	11mm	12mm	12mm	12mm
Rating - UL	600V/15A/14-20AWG	600V/20A/12-20 AWG	600V/25A/10-20AWG	600V/50A/8-16AWG
End Plate	DSEP2.5	DSEP 4	DSEP6	DSEP10
End Clamp	SCUSL OR DCKN			
Push-in 2 pole jumper	SSL2.5	SSL4	SSL6	SSL10
Labels	KN5	KN5.5	KN8	KN10
Color Gray (G); Red (R); Yellow(Y); Blue (B); Black (BL); Green (GR); Green-Yellow (GY)	DST2.5 (G); DST2.5 (R); DST2.5 (Y); DST2.5 (B); DST2.5 (BL); DST2.5 (GR); DST2.5 (GY)	DST4 (G); DST4 (R); DST4 (Y); DST4 (B); DST4 (BL); DST4 (GR); DST4 (GY)	DST6 (G); DST6 (R); DST6 (Y); DST6 (B); DST6 (BL); DST6 (GR); DST6 (GY)	DST10 (G); DST10 (R); DST10 (Y); DST10 (B); DST10 (BL); DST10 (GR); DST10 (GY)
Mounting Rail	3401/SE	3401/SE	3401/SE	3401/SE

Multi-connections and ground block				
	5mm	5mm	Ground blocks 6mm	5x20mm FUSE HOLDER (8mm)
Terminal Pitch	DCT 2.5-1x2	DCT 2.5-2x2	DSET4	DCF4
Height x Width in mm	40.50 x 50	40.50 x 50	34 x 59	64.8 x 60mm
Rated Cross section	2.5mm ²	2.5mm ²	4mm ²	4mm ²
Rating - UL	600V/15A/14-22 AWG	600V/15A/14-22 AWG	10-20 AWG	10-20 AWG
End Plate	DMP 2.5		DSEP 4	DFEP
Push-in 2 pole jumper	SSL 2.5			SSL4
Labels	KN 5		KN5.5	KN8

Side entry - Spring Clamp Terminal



	Terminal Pitch: 5mm (42.5mm wide x 35mm High)
	Rating: 600V; 15 Amps; 22-14 AWG ; Wire strip length: 8.5mm
	Accessories: SEP2.5 (end plate); SCUSL (end stopper)
	SSL2.5 (Push-in type shorting link); KN5 (Marking labels)