




Special Function Terminals

Terminals with switch <ul style="list-style-type: none"> • Assembled in the USA • 8 mm wide terminals • Available with ON-ON, ON-OFF-ON, ON-MOM and On-off-MOM functions • Approvals: <ul style="list-style-type: none"> ○ Made with UL recognized parts ○ CSA terminal block and cUL toggle switch (silver plated) • Fully insulated – no end barrier required • RoHS compliant 		
Technical data		
Contacts	Max. 1A/250V, 3A/120VAC or 28VDC	
Resistance of ON contacts	20mΩ max	
Wire size	12-24 AWG	
To be snapped on	Din 35mm or Din 32mm rail	
Size L x W x H	74 x 8 x 70 mm	
Tightening torque	7 LB-In	
Wire stripping length	9mm	
Order Numbers		
ON-ON (2 way)	ESG290T/2	
ON-OFF-ON (3 way)	ESG290T/3	
ON-MOM (2 way)	ESG290T/28	
ON-OFF-MOM (3 way)	ESG290T/328	
Accessories		
Insulated side jumper 10 pole	UFSL-10W	
Labels	KN8	

Disconnect Switch Terminals Knife disconnect terminal blocks		 Push-twist to hold
	KULTD 4	KUPTD6
Rating	UL 600V/ 15A; 10-24 AWG	IEC/CE 630V/24A/6mm ²
H x L x W (mm)	51 x 6 x 52	
End Plate/Partition	KPSD4/KBXF	End plate - KPPDS
Comb Link 10 way Labels	SLCM2.5-10W KN5.5	Side 2 way SLD6-2W KN8