






Special Function Terminals

Terminals with switch <ul style="list-style-type: none"> Assembled in the USA 8 mm wide terminals Available with ON-ON, ON-OFF-ON, ON-MOM and On-off-MOM functions Approvals: <ul style="list-style-type: none"> Made with UL recognized parts CSA terminal block and cUL toggle switch (silver plated) Fully insulated – no end barrier required RoHS compliant 			With LED  24VDC and 120VAC
Technical data			
Contacts	Max. 1A/250V, 3A/120VAC or 28VDC	Max. 1A/250V, 3A/120VAC or 28VDC	
Resistance of ON contacts	20mΩ max	20mΩ max	
Wire size	12-24 AWG	12-24 AWG	
To be snapped on	Din 35mm or Din 32mm rail	Din 35mm or Din 32mm rail	
Size L x W x H	74 x 8 x 70 mm	74 x 8 x 70 mm	
Tightening torque	7 LB-In	7 LB-In	
Wire stripping length	9mm		
Order Numbers			
ON-ON (2 way)	ESG290T/2	ESG290T/2-24VDCLED ESG290T/2-120VACLED	
ON-OFF-ON (3 way)	ESG290T/3		
ON-MOM (2 way)	ESG290T/28		
ON-OFF-MOM (3 way)	ESG290T/328		
Accessories			
Insulated side jumper 10P	UFSL-10W	UFSL-10W	
Labels	KN8	KN8	

Disconnect Switch Terminals Knife disconnect terminal blocks		 Push-twist to hold
	KULTD 4	KUPTD6
Rating	UL 600V/ 15A; 10-24 AWG	IEC/CE 630V/24A/6mm2
H x L x W (mm)	51 x 6 x 52	
End Plate/Partition	KPSD4/KBXF	End plate - KPPDS
Comb Link 10 way Labels	SLCM2.5-10W KN5.5	Side 2 way SLD6-2W KN8