



Bare collector terminals

25/6 mm²



- Terminal and pressure part of brass
- Screws and springs of stainless steel
- The connection between mounting rail and terminal as well as the connected conductors are protected against working loose
- 1 main terminal with clamp for through conductors up to 25 mm²
- 8 or 16 additional connections for conductors up to 6 mm²



Article numbers

	with 1 main connection up to 25 mm ² 10-25 mm ² /6-4AWG 8 additional connections up to 6 mm ² 2.5-6mm ² /18-8AWG	with 1 main connection up to 25 mm ² 10-25 mm ² /6-4AWG 16 additional connections up to 6 mm ² 2.5-6mm ² /18-8AWG
	3433	3434

Technical data

Connecting capacity		
- of the main terminal ∅ mm	7	7
- of the additional connections ∅mm	3.5	3.5
Clamping screws		
- of the main terminals	M5	M5
- of the additional connections	M3	M3
Central screws for pressure part	M3 (1 x)	M3 (2 x)
Strip insulation mm	7	7
Clamping couple for electric screw-driver		
for screws M5 Nm	4.0	4.0
for screws M3 Nm	0.8	0.8
Packing unit pcs	10	5

3

Accessories see pages 1.1.71 to 1.1.107



Mounting rail according to EN 60715 TH 35 7.3x1 No. 3401
corresponds to resistance to short-circuits of a conductor 16 mm²

Mounting rail according to EN 60715 TH 35 15x2.5 No. 3490
corresponds to resistance to short-circuits of a conductor 50 mm²

Mounting rail according to EN 60715 TH 35 15x2.3 Cu No. 80290
corresponds to resistance to short-circuits of a conductor 150 mm²