









## Earth Terminals (ATEX approved)

Earth terminal blocks replace conventional bus bars. Grounding is established through the foot which clamps directly on the Din rail. The conducting part is brass with nickel-tin plating providing a low resistance path					
	<b>Part No.</b>				
		<b>ET6</b>	<b>ET10</b>	<b>ET16</b>	<b>ET35</b>
	Wire Size	8-20 AWG	6-16 AWG	3-12 AWG	1-8 AWG
<b>Technical Data</b>					
Stripping length	13mm	13mm	13mm	17mm	
Screw tread/tightening torque	M3.5/14 Lb-in	M4/17 Lb-in	M4/14 Lb-in	M6/32Lb-in	
L/W/H mm	43x8x45.5	43x10x45.5	52x12.5.5x52	63x16.5x63	
<b>Accessories</b>					
End Cover	Not required				
Partition Plate	KBXF				
Making Label	KN8				
End Stopper	SCKN				

### Additional Earth terminals:

				
<b>Ratings</b>	<b>24-10AWG</b>	<b>24-10AWG</b>	<b>Collector Ground Blocks</b>	<b>Isolated Ground collector</b>
<b>Part No.</b>	EBT4	EBT 4TWIN	Grounds to the Din Rail	
Stripping length	10mm	8mm	<b>Part No. 3433</b> 1 main terminal for up to 4 AWG 8 additional terminals for up to 8AWG	<b>DBK1x4GY</b> 1 main terminal for up to 1 AWG 4 terminals (8 termination pts) for up to 6AWG
Screw tread/tightening torque	M3/5Lb-in	M3/5Lb-in	<b>Part No. 3434</b> 1 main terminal for up to 4 AWG 16 additional terminals for up to 8AWG	<b>DBK1x8GY</b> 1 main terminal for up to 1 AWG 8 terminals (16 termination pts) for up to 6AWG
L/W/H mm	42.5/6.2/47	36.75/6/46		
<b>Accessories</b>				
Labels	U6	U6		
End stopper	SCKN	SCKN		