


# DPSC 5.08 (2W to 8W)



## GENERAL DESCRIPTION

DPSC 5.08 is a Plug and Socket Connector with Screw Clamp Connection finding its application for quick isolation and in C&I Industry

### WIRE TERMINATION TECHNOLOGY

Spring Clamp

### PRODUCT FEATURE

1. Polyamide 6,6 Housing
2. Panel Mount Version
3. Wire to Wire Connection Version

### APPROVALS



## TECHNICAL DATA

### GENERAL

No of Levels	1
No of Connection	16
Colours	GREY,GREY,GREY,GREY,
Insulation Material	Polyamide 66
impulse Withstand Voltage	-
Pollution Degree	3 (IEC 60947-1)
Insulation Material Group	I
Nominal Voltage(V)	250 V
Nominal Current(A)	16 A
Width (In mm)	14.45 mm
Height (In mm)	26.15 mm
Conductor Cross Section (In sq mm)	2.5 sq mm sq mm
AWG Conductor Cross Section	Min: - AWG                      Max: - AWG
Stripping Length (In mm)	8.5 mm mm
Screw Thread	NA
Tightening Torque /Rated Torque (in Nm)	- Nm Nm

### KEY COMMERCIAL DATA

Standard Packing	20
Weight/Package	India
Custom Tariff No	India
Country of Origin	India

**ACCESSORIES**

**Marking Label**

**Label KN 5.08**



**Label KN 5.08**



**Label KN 5.08**

