




1, 2, 3, and 4 pole Relays



Relay bases for 1 and 2 pole relays Contact terminals all located on one side with the coil terminals on the opposite side		
Order No.	Relays ordered separately (see below)	
Base without LED	14F-2Z-C4	
Base with 24V LED	14F-2Z-C4-D1 (24V LED)	
Base with 120/230V LED	14F-2Z-C4-A1 (120/230V LED)	
Socket	10A/300V	
Socket wire size	22-10AWG	
Socket LxWxH mm	75.2x15.7x61.2	
 Side jumper	45740CC/8-F (8-way jumper link)	
Technical Data		
Relays	1PDT Order No.	2PDT Order No.
12VDC	45740R1/1-F (16A/250V)	45740R2/1-F
24VDC	45740R1/2-F (16A/250V)	45740R2/2-F
24VAC		45740R2/6-F
115VAC	45740R1/5- F (10A/250V)	45740R2/5-F
Current/voltage	above	8A/250V

2, 3 and 4 pole relays From Comat			
	2 pole; 10 Amp	3 pole; 10 Amp	New
			4 pole; 8A/250VAC LED, lockable man. op
24VDC	C2-A20/DC24V	C3-A30/DC24V	R4N-2014-23-1024-WTL
115VAC	C2-A20X/AC115V	C3-A30X/AC115V	R4N-2014-23-5120-WTL
Socket	EC-8	EC-11	GZT4
Please call for other voltages and features (LEDs, higher current, etc)			
			4 pole; 16Amps
			C5-A30/DC24
			C5-A30/AC115