

NEW

High Current Terminal Blocks

NEW

Electrotech Sales
www.esgllc-usa.com
(215) 997-8855

High Current Terminal Blocks Distribution Blocks


- Reversible snap-on cover
- For use with Cu + AL cables
- Ratings, approvals and screw torque settings marked on cover
- Plastic material conforming to UL94 V0
- Ready to use Marking Kit (L1, L2, L3, N, PE, +, -) supplied with every block




9D.01.5.080.0304 9D.01.5.125.0206 9D.01.5.175.0210




- 80 A
- 7 connections



- 125 A
- 8 connections



- 175 A
- 12 connections



INPUT WIRE SPECIFICATION (Solid/Stranded)

Number of input		3	1	2
Terminal diameter	Ømm	6.6	9.8	11.8
Min. wire size				
	mm ²	2.5	10	10
	AWG	14	8	6
Max. wire size				
	mm ²	16	35	70
	AWG	6	2	2/0
Wire input stripping length				
	mm	15	15	15
Tool		Posidriv - flat screwdriver	Allen Key	Allen Key
Tool dimension	mm	5.5/PZ2	4	5
Torque	Nm	1.5...2	3.5...5	6...10

OUTPUT WIRE SPECIFICATION (Solid/Stranded)

Number of output		4	1	6	10
Terminal diameter	Ømm	4.5	6.8	6.4	6.4
Min. wire size					
	mm ²	2.5	6	2.5	2.5
	AWG	14	10	14	14
Max. wire size					
	mm ²	6	16	16	16
	AWG	10	6	6	6
Wire input stripping length					
	mm	11	11	11	11
Tool		Posidriv - flat screwdriver	Allen Key	Posidriv-flat screwdriver	Posidriv - flat screwdriver
Tool dimension	mm	4/PZ1	3	5.5 PZ2	5.5/PZ2
Torque	Nm	0.8...12	2...3	2...3	2...3